

Wayne®

Paragon

Hard Floor Seal and Finish



Ideal for use on quarry tile, terrazzo, slate, ceramic floors

Easy to apply and maintain

Beautifies, intensifies colors, never yellows

Adheres to dense surfaces

Urethane fortified for maximum durability

One product Spectacular floors

Paragon is a new, urethane fortified, sealer finish designed to protect and beautify stone, slate, quarry tile and ceramic floors. It has exceptional adhesion characteristics that enhance its ability to bond with high density, low porosity surfaces and provide long term durability under conditions where conventional sealers fail.

Paragon applies easily and levels to a beautiful, rich gloss. Once dry, it resists dirty and tracked in soils for maximum protection of decorative stone flooring. When repairs are necessary, Paragon can be restored to a like new appearance by recoating, spray buffing or high speed burnishing.

Manufactured by:

**Wayne Concept Manufacturing Co., Inc.
Fort Wayne, IN 46825 219-482-8615**

Copyright: 10/1997

Serving the maintenance community for over 60 years

Wayne®

Paragon

Hard Floor Seal and Finish

DIRECTIONS FOR USE

Initial application

1. Strip floor of all old finish and seal.
2. Rinse thoroughly and allow to dry.

Note: It is very important that floors be completely dry when Paragon is applied. Cement matrix between quarry and ceramic tile may retain chemical residues for several hours after stripping.

3. Apply a medium coat with a clean applicator or synthetic applicator mop.
4. Allow to dry completely before applying additional coats.
5. Apply additional coats as required to build desired appearance.

Recoating

1. Clean floor thoroughly to remove surface dirt, scuff or heel marks. If floors are extremely dirty, the use of a floor machine equipped with an abrasive pad or nylon scrub brush might be required.
2. Rinse thoroughly and allow to dry.
3. Apply a medium coat with a clean applicator or synthetic applicator mop.

High Speed Maintenance

On smooth stone floors like terrazzo, Paragon can be burnished to a dazzling luster with electric or propane equipment. To insure optimum response, clean floor with Wayne Auto Prep Cleaner and Conditioner before polishing.

Notes: On uneven flooring like slate or quarry tile, the use of synthetic polishing and scrubbing brushes instead of abrasive pads will provide superior results.

Due to the almost total lack of porosity on glazed ceramic tile, an adhesion test should be run before application. Your Wayne Representative will be happy to assist you.

We do not recommend the use of this or any other sealer on stone floors in kitchens where cooking oils might cause slippery conditions.

Specifications

Non-volatile solids	18%
Fragrance	Mild acrylic
Color (Liquid)	Milky white
Color (Dried film)	Water clear
Density	8.56#/gal.
Water resistance	Excellent
Detergent resistance (ASTM D3207)	Excellent
Soil resistance (ASTM D3206)	Excellent
Slip resistance (ASTM D2047)	>0.50 COF
Cure time (75°F, 50% R.H.)	30 min.
Recoat time (75°F, 50% R.H.)	35-40 min.
pH	8.6-9
Flash point	None
Coverage	1500-2000 sq. ft./gal.