

5005 Speedway Drive  
 Fort Wayne, IN 46825  
 Phone 260-482-8615  
 Fax 260-483-5598

# Spot Out II

**EMERGENCY  
 INFOTRAC 800-535-5053**

## SAFETY DATA SHEET

### SECTION 1 - IDENTIFICATION

Product Name..... Spot Out II	Cas#: N/A, Preparation
SDS#.....940	
Chemical Name..... N/A, Preparation	
Chemical Family..... Peroxide	Date Prepared: 2/18/14
Hazard Classification.....N/A, Preparation	Last Revised: 02/08/21
Product Use.....Water Based Stain Remover, For Industrial Use Only	

### SECTION 2 – HAZARDS IDENTIFICATION

#### EMERGENCYOVERVIEW

**Color:** Clear  
**Physical State:** liquid  
**Odor:** fruity



#### POTENTIAL HEALTH EFFECTS

**Primary routes of exposure:** Skin contact and inhalation.  
**Signs and symptoms of acute exposure:** The product, in the form supplied, is not anticipated to produce significant adverse human health effects.  
**Acute Eye:** Slightly irritating. (data for solvent component)  
**Acute Skin:** Slightly irritating. (data for solvent component)  
**Remarks:** Handle in accordance with good industrial hygiene and safety practice. Dried product may stick to the skin causing irritation upon removal.

### SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS NUMBER	INGREDIENT % RANGE
Hydrogen Peroxide	7722-84-1	1-5 %
Ethylene Glycol Monobutyl Ether	111-76-2	1 – 5
Acrylate Copolymer	Trade Secret	1-5
Propylene glycol monomethyl ether	107-98-2	1 - 5

### SECTION 4 – FIRST AID MEASURES

**Eyes:** Immediately flush eye(s) with plenty of water.  
**Skin:** In case of contact, Immediately flush skin with plenty of water. Remove material from clothing. Wash clothing before reuse. Thoroughly clean shoes before reuse.  
**Ingestion:** If swallowed, DO NOT induce vomiting. Get medical attention. Never give anything by mouth to an unconscious person.  
**Inhalation:** If inhaled, remove victim to fresh air.

## SECTION 5 – FIRE FIGHTING MEASURES

### FIRE HAZARD DATA:

**Flash Point and Method:** None

**Flammability Limits (vol/vol%):** LOWER: No data available      UPPER: No data available

**Extinguishing Media (suitable):** Carbon dioxide (CO<sub>2</sub>), Dry chemical, Foam, water spray

**Protective Equipment:** Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand/NIOSH approved or equivalent).

**Further Firefighting Advice:** Fire fighting equipment should be thoroughly decontaminated after use.

**Fire and Explosion Hazards:** When burned, the following hazardous products of combustion can occur:

Carbon oxides

Hazardous organic compounds

## SECTION 6 – ACCIDENTAL RELEASE MEASURES

**In case of spill or leak:** Prevent further leakage or spillage if you can do so without risk. Ventilate the area. Avoid generation of vapors. Contain and collect spillage with non-combustible absorbent material such as clean sand, earth, diatomaceous earth or non-acidic clay and place into suitable properly labeled containers for prompt disposal. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

## SECTION 7 – HANDLING AND STORAGE

**Handling:** Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of material from eyes, skin, and clothing.

**Storage:** Keep in a dry, cool place. This material is not hazardous under normal storage conditions; however, material should be stored in closed containers, in a secure area to prevent container damage and subsequent spillage. Store in upright position only. Keep container closed when not in use.

**Storage Stability:** Stable under normal conditions. May coagulate if frozen at 0°C (32°F). Material may develop bacteria odor on long term storage.

### Storage Incompatibility - General:

Store separate from: Strong bases, Strong oxidizing agents, Strong acids

May cause coagulation: Multivalent metal salts

**Temperature tolerance – Do not store below:** - 34 °F (1 °C)

**Temperature tolerance – Do not store above:** 100 °F (38 °C)

## SECTION 8 – EXPOSURES CONTROLS/PERSONAL PROTECTION

### Airborne Exposure Guidelines:

#### Hydrogen Peroxide

US. Workplace Environmental Exposure Level (WEEL) Guides

Time Weighted Average (TWA): 1 ppm (PEL): 1 ppm

#### Propylene glycol monomethyl ether

ACGIH (TWA): 100 ppm

#### Ethylene Glycol Monobutyl Ether

ACGIH (TWA): 20 ppm

Only those components with exposure limits are printed in this section. Limits with skin contact designation above have skin contact effect. Air sampling alone is insufficient to accurately quantify exposure. Measures to prevent significant cutaneous absorption may be required. Limits with a sensitizer designation above mean that exposure to this material may cause allergic reactions. **Engineering Controls:** Investigate engineering techniques to reduce exposures below airborne exposure limits or to otherwise reduce exposures. Provide ventilation if necessary to minimize exposures or to control exposure levels to below airborne exposure limits (if applicable see above). If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

**Respiratory Protection:** Avoid breathing vapor or mist. Where airborne exposure is likely or airborne exposure limits are exceeded (if applicable, see above), use NIOSH approved respiratory protection equipment appropriate to the material and/or its components (full facepiece recommended). Consult respirator manufacturer to determine appropriate type equipment for a given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where there may be a potential for significant exposure or where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

**Eye/Face Protection:** Use good industrial practice to avoid eye contact.

**Skin Protection:** Minimize skin contamination by following good industrial hygiene practice. When handling this material, gloves of the following type(s) should be worn: Neoprene, nitrile, Polyvinylchloride, Natural Rubber, butyl-rubber, Chlorinated polyethylene, polyethylene (PE), ethyl vinyl alcohol laminate (EVAL).

## SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

<b>Color:</b>	clear	<b>Vapor Density:</b>	Greater than air
<b>Physical State:</b>	liquid	<b>Vapor Pressure:</b>	Not determined
<b>Odor:</b>	fruity	<b>Boiling Point:</b>	Not determined
<b>pH:</b>	5 – 5.5 ±0.5	<b>Freezing Point:</b>	32 °F (0 °C) (data for Water (7732-18-5))
<b>Density:</b>	calculated 8.46 ±0.05 #/gal	<b>Solubility in water:</b>	complete
<b>Specific Gravity, g/ml:</b>	calculated 1.017 ±0.005 Water=1 (liquid)		

## SECTION 10 – STABILITY AND REACTIVITY

**Stability:** This material is chemically stable under normal and anticipated storage, handling and processing conditions.

**Stability-Conditions to avoid:** See HANDLING AND STORAGE section of this MSDS for specified conditions. See Hazardous Decomposition Products below.

**Materials to Avoid:** Strong acids, Strong bases, Strong oxidizing agents

May cause coagulation: Multivalent metal salts

**Hazardous Decomposition Products:** Thermal decomposition giving flammable and toxic products : Hazardous organic compounds, Carbon oxides

**Hazardous Polymerization:** Hazardous polymerization does not occur.

## SECTION 11 – TOXICOLOGICAL INFORMATION

### Toxicity Data:

<u>Component</u>	<u>Oral: LD50</u>	<u>Dermal: LC50</u>	<u>Inhalation: LC50</u>
Hydrogen Peroxide	>5,000 mg/kg (Rat)	>2,000 mg/kg (Rabbit)	>0.17 mg/l @50% (Rat)
Ethylene Glycol Monobutyl Ether	1.2 g/kg (Guinea Pig)	400-500 mg/kg (Rabbit)	>633ppm (Guinea Pig)
Propylene Glycol Monomethyl Ether	5,660 mg/kg (Rat)	13 g/kg (Rabbit)	7000 ppm/6 hours (Rat)

### CARCINOGENICITY:

<u>Chemical Name</u>	<u>IARC</u>	<u>NTP</u>	<u>OSHA</u>	<u>Other</u>
Hydrogen Peroxide	Listed	Not listed	Not listed	(ACGIH) Listed (A3, Animal Carcinogen)

## SECTION 12 – ECOLOGICAL INFORMATION

### Chemical Fate and Pathway

Hydrogen peroxide in the aquatic environment is subject to various reduction or oxidation processes and decomposes into water and oxygen. Degrades in the atmosphere within the light spectrum with hydroxyl radicals in the gas phase and subsequent photolysis.

### ECOTOXICOLOGICAL INFORMATION:

#### Hydrogen Peroxide

Channel catfish 96-hour LC50 = 37.4 mg/L Fathead minnow 96-hour LC50 = 16.4 mg/L

Daphnia magna 24-hour EC50 = 7.7 mg/L

Daphnia pulex 48-hour LC50 = 2.4 mg/L

Freshwater snail 96-hour LC50 = 17.7 mg/L

## SECTION 13 – DISPOSAL CONSIDERATIONS

### Waste disposal:

Disposal via incineration is recommended. Dispose of in accordance with federal, state and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

## SECTION 14 – TRANSPORT INFORMATION

DOT/IMDG/IATA Hazard Classification: Non-Hazardous, not regulated

Hazardous: N

Shipping Name: LIQUID CLEANING COMPOUNDS

Freight Class: 55

## SECTION 15 – REGULATORY INFORMATION

US. Toxic Substances Control Act TSCA The components of this product are all on the TSCA Inventory.

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 144) DSL This product contains one or several components that are not on the Canadian DSL nor NDSL lists.

### United States – Federal Regulations

#### SARA Title III – Section 302 Extremely Hazardous Chemicals:

No SARA Hazards

#### SARA Title III - Section 311 Hazard Categories:

Propylene glycol monomethyl ether: acute health and fire hazard

#### SARA Title III - Section 312 Hazard Categories:

The Threshold Planning Quantity (TPQ) for this product, if treated as a mixture, is 10,000 lbs; however, this product contains the following ingredients with a TPQ of less than 10,000 lbs.:  
None, (conc. <52%)

#### SARA Title III – Section 313 Toxic Chemicals:

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantity (RQ): Not listed

## SECTION 16 – OTHER INFORMATION

### HMIS Rating

KEY: 4=Severe, 3=Serious, 2=Moderate, 1=Slight, 0=Minimal  
Protection=B (Safety goggles, gloves,)

HMIS – Hazardous Materials Identification System

<b>HEALTH</b>	<b>1</b>
<b>FLAMMABILITY</b>	<b>0</b>
<b>REACTIVITY</b>	<b>0</b>
<b>PROTECTIVE EQUIPMENT</b>	<b>B</b>

## PREPARATION INFORMATION

Wayne Concept believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use are beyond the control of Wayne Concept, Wayne Concept expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.