

# Single Motor Upright Vacuum



## The smart alternative to high priced, unreliable commercial vacuums.

### Reduce maintenance costs and downtime

The V-SMU-14 eliminates the four key issues that cause vacuums to fail, thus increasing productivity and lowering service costs versus current commercial vacs.

### Healthy, proven performance

Standard with HEPA 3-stage filtration, the vacuum's cleaning performance is also certified Silver by the Carpet and Rug Institute's (CRI) Seal of Approval program.

### Durable and Affordable

Major components have been proven in commercial applications for over 10 years. This vacuum delivers high value at operating costs up to 58% less than other commercial vacuums.

Be smart. Try this new alternative to the high-priced, unreliable commercial vacuums. It will change your vacuum reality.

## Key Benefits

- LEED qualifying with CRI SOA Silver Performance and noise levels less than 70 dBA
- Increase productivity and cleaning coverage with on-board crevice and upholstery tools and up to 30% longer wand reach than competition.
- Easy operator serviceability with no-tool brush and belt replacement



# Single Motor Upright Vacuum



Features	Specifications*
<b>Product Name</b>	V-SMU-14
<b>Vacuum System</b> Airflow at 2 in / 50 mm orifice Vacuum motor hp Vacuum motor type Vacuum motor watts/amps Water lift at sealed orifice	120 cfm / 3.4 m <sup>3</sup> /h 1.6 hp / 1.19 kW each Single stage, thermal protected, clean air 1200 watts / 10 A 89 in / 2260 mm
<b>Brush Drive System</b> Brush belt description Brush type Brush size Brush motor HP Brush height	Round drive belt 12 in / 305 mm metal brush roll with natural bristles 2.25 / 57 mm in diameter, 12 in / 305 mm length 0.25 hp / .19 kW Automatic, self-adjusting
<b>Filtration</b> Triple filtration system Triple filtration description Vacuum bag capacity	Filter bag, vac motor filter, and HEPA filter High efficiency (99.97%) at 0.3 micron Fill design, 3.8 qt / 3.6 L
<b>Electrical</b> Electrical system Power cord length	Printed circuit board protected 50 ft / 15 m, 3 wire commercial safety-yellow cord with thermal protection switch
<b>Chassis/Body Construction</b> Construction	Injection molded ABS
<b>Accessories</b> Standard	On-board crevice tool, dusting brush with telescopic aluminum wand with 15' reach (4:1 stretch)
<b>Dimensions / Weight / Sound Level</b> Length Width Height Weight Sound level (at operator's ear)	12.5 in / 320 mm 14.75 in / 370 mm 44 in / 1120 mm 16 lb / 7.3 kg 69.9 dBA
<b>Approvals</b>	ETL, (US/C)
<b>Warranty</b>	See your sales representative or authorized distributor for complete warranty details.

\*Specifications subject to change without notice